(43) International Publication Date 7 April 2005 (07.04.2005)

(51) International Patent Classification7:

(10) International Publication Number WO 2005/031244 A1

C04B 38/00 (21) International Application Number:

F41H 5/04,

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

(22) International Filing Date:

PCT/DK2004/000655 28 September 2004 (28.09.2004)

English

(25) Filing Language:

English (26) Publication Language:

(30) Priority Data:

29 September 2003 (29.09.2003) DK PA 2003 01410

(71) Applicant (for all designated States except US): DEMEX RADGIVEN DE INGENIØRER A/S [DK/DK]; 2, Sortemosevej, DK-3400 Allerød (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): LAURITZEN, Erik, K. [DK/DK]; 16 Egernvej, DK-2000 Frederiksberg F (DK).

(74) Agent: CHAS. HUDE A/S; 33, H.C. Andersens Boulevard, DK-1780 Copenhagen V (DK).

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, 7W. (84) Designated States (unless otherwise indicated, for every

kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AN ASSEMBLY FOR PROTECTION AGAINST AN EXPLOSION



(57) Abstract: An assembly for protection against explosion in form of a substantially plate-shaped multi-ply element includes two or outer walls (1, 2) and at least one intermediate layer of a ceramic material presenting a density in the range of approximately 0.3 to 1.5 g/cm³, a pore diameter in the range of approximately 20 to 120µ and a physical extent in the range of approximately 0.5 to 10 nm.

2005/031244 A1